NSN 5905-00-376-0108

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-376-0108

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Overall Length:

Between 1.276 inches and 1.340 inches

Terminal Length:

Between 0.469 inches and 0.531 inches

Overall Height:

Between 0.769 inches and 0.861 inches

Overall Width:

Between 0.180 inches and 0.200 inches

Mounting Hole Diameter:

Between 0.088 inches and 0.098 inches

Shaft Diameter:

Between 0.100 inches and 0.130 inches

Shaft Length:

Between 0.036 inches and 0.080 inches

Body Length:

Between 1.240 inches and 1.260 inches

Body Width:

Between 0.180 inches and 0.200 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Center To Center Distance Between Terminals:

Between 0.890 inches and 0.910 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.995 inches and 1.005 inches

Mounting Facility Quantity:

2

Electrical Resistance Per Section:

50.000 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

NSN 5905-00-376-0108

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0