Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-378-0436

## Section Quantity:

1

Body Style:

Rectangular

### **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.200 inches

#### Shaft Diameter:

0.100 inches

#### Shaft Length:

0.060 inches

#### Body Length:

0.750 inches

#### **Body Width:**

0.190 inches

# Body Height:

0.340 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

5400.0

#### **Center To Center Distance Between Terminals:**

0.700 inches

#### **Terminal Location:**

Lower adjacent side two rows

#### **Mounting Method:**

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

### **Features Provided:**

Nonmetallic shaft

## **Electrical Resistance Per Section:**

500.0 ohms single section

## Rotary Actuator Travel In Angular Deg:

5400.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# NSN 5905-00-378-0436 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

#### Power Dissipation Rating Per Section In Watts:

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0