Nonprecision Wire Wound Variable Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-00-388-92 | 244 |
|---|-------------|
| Section Quantity: | |
| 1 | |
| Overall Length: | |
| 1.656 inches | |
| Shaft Diameter: | |
| 0.250 inches | |
| Shaft Length: | |
| 0.500 inches | |
| Overall Diameter: | |
| 0.750 inches | |
| Shaft Style: | |
| Round | |
| Actuator Type: | |
| Single shaft | |
| Effective Electrical Rotation In Deg Angular Rotation: | |
| 3600.0 | |
| Screw Thread Diameter: | |
| 0.375 inches | |
| Screw Thread Series Designator: | |
| Unef | |
| Screw Thready Qty Per Inch (tpi): | |
| 32.0 | |
| Mounting Method: | |
| Standard bushing | |
| Electrical Resistance Per Section: | |
| 10.000 kilohms single section | |
| Rotary Actuator Travel In Angular Deg: | |
| 360.0 | |
| Function Conformity Tolerance Per Section: | |
| -0.50 to 0.50 single section | |
| Power Dissipation Rating Per Section In Watts: | |
| 3.0 free air single section | |
| Resistance Tolerance Per Section In Percent: | |
| -5.0 to 5.0 single section | |
| Actuator Travel Control Feature: | |
| Continuous motion | |
| Function Characteristic Per Section: | |
| Single section linear | |
| Ambient Tempurature In Deg Celsius Per Section At Full R | ated Power: |
| 125.0 single section | |
| Standard Taper Curve Per Section: | |
| A single section | |
| | |

AeroBase Group

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0