

View Online at <https://aerobasegroup.com/nsn/5905-00-390-9669>

Section Quantity:

2

Body Style:

Cylindrical studs mounted

Reliability Indicator:

Not established

Overall Length:

2.406 inches

Body Diameter:

2.000 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

2.040 inches

Overall Diameter:

1.990 inches

Mounting Hole/stud Circle Diameter:

1.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

352.0

Maximum Starting Torque:

2.00 inch-ounces

Maximum Running Torque:

2.00 inch-ounces

Screw Thread Diameter:

0.138 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

3

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

20.0 percent, rated amperes c and better industrial clears

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.35/+0.35 2nd section

Power Dissipation Rating Per Section In Watts:

4.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 1st section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

65.0 all sections

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0