NSN 5905-00-392-5482

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-392-5482 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.688 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.249 inches **Shaft Length:** 0.938 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.562 inches **Overall Diameter:** 0.875 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 50.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:**

Electrical Resistance Per Section: 50.0 kilohms single section

Standard bushing

NSN 5905-00-392-5482

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
3600.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
1 tab, solder lug and 1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0