## NSN 5905-00-392-9424

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-392-9424

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0  Electrical Resistance: 150.000 ohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: A001a0	
Electrical Resistance:  150.000 ohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0  Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-20.0/+20.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Electrical Resistance:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	150.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+125.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: Between 0.090 inches and 0.110 inches  Body Length: Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fiig:	-55.0/+125.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: Between 0.090 inches and 0.110 inches  Body Length: Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Hermetically sealed
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: Between 0.090 inches and 0.110 inches Body Length: Between 0.185 inches and 0.235 inches Power Dissipation Rating In Watts: 0.250 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Not established  Terminal Length: 2.000 inches  Body Diameter:  Between 0.090 inches and 0.110 inches  Body Length:  Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Wire lead
Terminal Length:  2.000 inches  Body Diameter:  Between 0.090 inches and 0.110 inches  Body Length:  Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts:  0.250 free air  Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Reliability Indicator:
2.000 inches  Body Diameter:  Between 0.090 inches and 0.110 inches  Body Length:  Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Not established
Body Diameter:  Between 0.090 inches and 0.110 inches  Body Length:  Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Length:
Between 0.090 inches and 0.110 inches  Body Length: Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator: Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	2.000 inches
Body Length:  Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts:  0.250 free air  Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
Between 0.185 inches and 0.235 inches  Power Dissipation Rating In Watts: 0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Between 0.090 inches and 0.110 inches
Power Dissipation Rating In Watts:  0.250 free air  Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
0.250 free air  Cubic Measure (non-core): 0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.185 inches and 0.235 inches
Cubic Measure (non-core):  0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
0.002 cubic inches  Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.250 free air
Style Designator:  Axial terminal each end  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Cubic Measure (non-core):
Axial terminal each end  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.002 cubic inches
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<u></u>
Fiig:	Demilitarization:
-	No
-	Fiig:
	-