NSN 5905-00-394-1189

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-394-1189

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Overall Length:
0.415 inches
Terminal Length:
0.172 inches
Overall Height:
0.547 inches
Overall Width:
0.161 inches
Shaft Diameter:
Between 0.050 inches and 0.075 inches
Shaft Length:
0.040 inches
Body Length:
0.375 inches
Body Width:
0.161 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Maximum Starting Torque:
5.00 inch-ounces
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

NSN 5905-00-394-1189

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**