NSN 5905-00-399-7762

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-399-7762 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** Between 1.995 inches and 2.005 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.969 inches and 1.031 inches **Body Length:** 3.079 inches **Mounting Lip Diameter:** Between 1.9950 inches and 2.0050 inches **Mounting Lip Depth:** Between 0.0880 inches and 0.0980 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 2.25 inch-ounces **Shaft End Play:** 0.005 inches

Shaft Runout: 0.001 inches

NSN 5905-00-399-7762

No

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Puncuts
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
20.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-2.00/+2.00 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
2.5 free air all sections
Function Conformity Per Section:
All sections terminal base linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections graph
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Test Data Document:
10001-2091272 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
15 turret
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

NSN 5905-00-399-7762

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0