NSN 5905-00-400-1530

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-400-1530 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.715 inches **Terminal Length:** Between 0.285 inches and 0.315 inches **Overall Height:** Between 0.360 inches and 0.380 inches **Overall Width:** Between 0.145 inches and 0.155 inches **Shaft Diameter:** 0.060 inches **Shaft Length:** 0.040 inches **Body Length:** Between 0.360 inches and 0.380 inches **Body Width:** Between 0.145 inches and 0.155 inches **Body Height:** Between 0.360 inches and 0.380 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Terminal Location:** Left adjacent side single row **Mounting Method: Terminal Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.090 inches and 0.110 inches

NSN 5905-00-400-1530

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**