Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-400-1573

# Section Quantity:

1

Body Style:

Cylindrical

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.785 inches

#### **Body Length:**

0.453 inches

#### Actuator Type:

Flush drive with slot-hole

## Maximum Stop Torque:

## 64.00 inch-ounces

#### **Terminal Location:**

Rear end

# Mounting Method:

Tab

#### Features Provided:

Nonmetallic shaft

#### **Electrical Resistance Per Section:**

1.0 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

Between 265.0 and 275.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

#### **Actuator Travel Control Feature:**

Continuous motion

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

#### Standard Taper Curve Per Section:

A single section

#### **Terminal Type And Quantity:**

3 tab, solder lug

### Shelf Life:

N/a

#### Unit Of Measure:

--

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0