Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-400-1699

# Section Quantity:

1

Body Style:

Rectangular

# Reliability Indicator:

Not established

#### **Terminal Length:**

0.300 inches

#### Shaft Diameter:

0.070 inches

#### Shaft Length:

0.060 inches

#### Body Length:

0.375 inches

#### Body Width:

0.145 inches

# Body Height:

0.375 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Grounded contact arm

#### **Electrical Resistance Per Section:**

20.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

9000.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

# NSN 5905-00-400-1699

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

1.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

# Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

#### Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A002a0