## NSN 5905-00-400-2143

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-400-2143

| Electrical Resistance: 38.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established |
|---|
| Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:   |
| Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:   |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:  |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator:  |
| Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:   |
| Terminal Type:  Wire lead  Reliability Indicator:   |
| Wire lead  Reliability Indicator:   |
| Reliability Indicator:  |
|   |
| Not established   |
|   |
| Terminal Length:  |
| 2.000 inches  |
| Body Diameter:  |
| 0.105 inches  |
| Body Length:  |
| 0.281 inches  |
| Power Dissipation Rating In Watts:  |
| 0.050 free air  |
| Cubic Measure (non-core):   |
| 0.002 cubic inches  |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;   |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |