NSN 5905-00-400-2190

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-400-2190

Electrical Resistance: 43.000 kilohms Resistance Tolerance in Percent: -0.100/4-0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: -0.105 inches Body Length: -0.281 inches Power Dissipation Rating In Watts: -0.085 free air Cubic Measure (non-core): -0.092 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Lifte: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
43.000 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.080 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Availa terminal each end Test Data Document: 004817-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Notal Unit of Measure:	-15.0/+15.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -0.000 inches Body Diameter: -0.105 inches Body Length: -0.015 inches Power Dissipation Rating In Watts: -0.050 free air Cubic Measure (non-core): -0.002 cubic inches Style Designator:	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	43.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wirre lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.281 inches Power Dissipation Rating In Watts: 0.095 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	125.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	145.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Terminal Type:
Note established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2.000 inches
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.105 inches
Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.281 inches
Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.050 free air
Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cubic Measure (non-core):
Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.002 cubic inches
Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.,
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0