## NSN 5905-00-400-2867

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-400-2867

-15.0/415.0 Electrical Resistance: 220.600 ohms Resistance Tolerance In Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/415.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/415.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Syle Designator: Akial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 220.600 ohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Ength: -2.000 inches Body Diameter: -0.130 inches Body Length: -0.380 inches Power Dissipation Rating In Watts: -0.100 ree air Style Designator: -Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: No Unit Of Measure: - Demilitarization: No Flig:	
220.600 ohms  Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.380 inches Power Dissipation Rating In Watts: 0.100 ree air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Na Unit Of Measure:	
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/±145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 0e4841-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	220.600 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.1400 free air Style Designator: Axial terminal each end Test Data Document: 60481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Diameter: 0.130 inches  Power Dissipation Rating in Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Flig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inciosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Diameter: 0.130 inches  Body Diameter: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-66.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Avial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A001a0	-65.0/+145.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-91213 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Encapsulated
Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length:  2.000 inches  Body Diameter:  0.130 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Reliability Indicator:
2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Not established
Body Diameter:  0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	Terminal Length:
Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	2.000 inches
Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Diameter:
O.380 inches  Power Dissipation Rating In Watts: O.100 free air  Style Designator:  Axial terminal each end  Test Data Document: O6481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.130 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
O.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.380 inches
Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.100 free air
Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Style Designator:
06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	<del></del>
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0