NSN 5905-00-400-3102

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-400-3102

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 15.0/+15.0 Electrical Resistance: 234.100 ohms Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Retiability Indicator: Not established Terminal Length: 2.000 inches 3.0dy Diameter: 2.130 inches 3.0dy Length: 3.380 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Length: 0.130 inches Body Length: 0.380 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
65.0/+145.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Not established Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Ferminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches
Body Diameter: 0.130 inches Body Length: 0.380 inches
0.130 inches Body Length: 0.380 inches
Body Length: 0.380 inches
0.380 inches
Power Dissination Rating In Watts:
ower bissipation rating in watts.
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A001a0