## NSN 5905-00-400-3121

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-400-3121

Electrical Resistance: 241.600 ohms Resistance Tolerance In Percent: -0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (fils is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
241.600 ohms  Resistance Tolerance in Percent: -0.100/40-100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0  Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: -0.000 inches  Body Diameter: -0.130 inches  Body Length: -0.380 inches  Body Length: -0.380 inches  Flower Dissipation Rating in Watts: -0.100 free air  Style Designator: Axial terminal each end Test Data Document: -0.6481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: No  Unit of Measure:	-15.0/+15.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Unameter: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No Unit Of Measure:	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	241.600 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  65.0/+145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  2.000 inches  Body Diameter:  0.130 inches  Body Diameter:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal end Celsius is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  Nia  Unit Of Measure:  Demilitarization:  No  Flig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -65.0/+145.0  Inciosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/A  Unit of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 fee air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Filg:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 Inches Body Diameter: 0.130 Inches Body Length: 0.380 Inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-65.0/+145.0
Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Axial terminal each end  Test Data Document: 06481-91213 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Encapsulated
Reliability Indicator:  Not established  Terminal Length: 2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No Flig:	Terminal Type:
Note stablished Terminal Length: 2.000 inches Body Diameter: 0.130 inches Body Length: 0.380 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Terminal Length:  2.000 inches  Body Diameter:  0.130 inches  Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Flig:	Reliability Indicator:
2.000 inches  Body Diameter: 0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure: Demilitarization: No  Fig:	Not established
Body Diameter:  0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	Terminal Length:
0.130 inches  Body Length: 0.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	2.000 inches
Body Length:  0.380 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	Body Diameter:
O.380 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator:  Axial terminal each end  Test Data Document: 06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	0.130 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
O.100 free air  Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.380 inches
Style Designator:  Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	0.100 free air
Test Data Document:  06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Style Designator:
06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-912113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.,
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0