

View Online at <https://aerobasegroup.com/nsn/5905-00-400-8988>

Section Quantity:

3

Body Style:

Cylindrical bushing mounted

Overall Length:

6.812 inches

Terminal Length:

0.344 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.812 inches

Body Length:

6.000 inches

Overall Diameter:

2.156 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

9.00 inch-ounces

Maximum Running Torque:

9.00 inch-ounces

Maximum Stop Torque:

550.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.562 inches

Shaft End Play:

0.00500 inches

Shaft Runout:

0.0005 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 1st section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 1st section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-800.0/+800.0 1st section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0