

View Online at <https://aerobasegroup.com/nsn/5905-00-400-8998>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Overall Length:

Between 2.620 inches and 2.870 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Mounting Bushing Length:

Between 0.290 inches and 0.330 inches

Body Length:

Between 1.870 inches and 2.030 inches

Overall Diameter:

2.170 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

550.00 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.552 inches and 0.572 inches

Shaft End Play:

0.00500 inches

Shaft Runout:

0.005 inches

Lateral Runout:

0.003 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.003 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Test Data Document:

07217-629860 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0