## NSN 5905-00-400-9787

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-400-9787

View Online at https://aerobasegroup.com/nsn/5905-00-400-9787
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-10.0/+10.0
Electrical Resistance:
3.570 kilohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.500 inches
Body Diameter:
Between 0.360 inches and 0.390 inches
Body Length:
Between 0.718 inches and 0.770 inches
Power Dissipation Rating In Watts:
0.333 free air
Cubic Measure (non-core):
0.083 cubic inches
Unpackaged Unit Weight:
5.000 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39005/2 government specification
Shelf Life:
N/a

--

**Unit Of Measure:** 

## NSN 5905-00-400-9787

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A001a0