NSN 5905-00-400-9902

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-400-9902

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.375 inches
Body Diameter:
0.344 inches
Body Length:
0.225 inches
Overall Diameter:
0.344 inches
Switch Type:
Rotary
Switch Voltage Rating In Volts:
120.0
Actuator Type:
Flush drive with slot-hole
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Terminal Location:
Rear end
Mounting Method:
Terminal
Features Provided:
Switch
Electrical Resistance Per Section:
200.000 ohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0 to 250.0 single section
Power Dissipation Rating Per Section In Watts:
0.125 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section

NSN 5905-00-400-9902

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Switch Current Type And Rating In Amps:
1.500 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0