

View Online at <https://aerobasegroup.com/nsn/5905-00-401-6664>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.281 inches

**Flat Height:**

0.216 inches

**Body Diameter:**

1.500 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.000 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.375 inches

**Shaft Style:**

Round, flatted

**Switch Type:**

Push-pull

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Nonturn Device Location:**

At 3 oclock

**Nonturn Device Radius:**

0.531 inches

**Switch Operating Position:**

Any position of rotation travel

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

50.0 ohms single section

**Rotary Actuator Travel In Angular Deg:**

297.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

80.0 single section

**Power Dissipation Rating Per Section In Watts:**

3.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Switch Current Type And Rating In Amps:**

1.000 ac

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0