NSN 5905-00-401-8997

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-401-8997

Electrical Resistance: 21.700 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Retiability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 9.015 inches Body Length: 9.0281 inches Power Dissipation Rating In Watts: 9.0281 inches Power Dissipation Rating In Watts: 9.0290 cubic inches Style Designator: Aktal terminal each end Test Data Document: 96481-912115 drawing (fihis is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Not Unit of Measure: Unit of Measu	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
21.700 kilohms Resistance Tolerance in Percent: -0.100/40-100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Akial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Nota Unit of Measure:	-15.0/+15.0
Resistance Tolerance in Percent: -0.100/+0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating in Watts: 0.0281 inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Note United Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire laed Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.050 free air Cubic Measure (non-core): 0.0481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	21.700 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.281 inches Power Dissipation Rating In Watts: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.005 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.002 cubic inches Style Designator: Axial terminal each end Fest Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	125.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Boddy Diameter: 0.105 inches Boddy Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Terst Data Document: 004841-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	145.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.080 ree air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 00481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type:
Note established Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Wire lead
Terminal Length: 2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Reliability Indicator:
2.000 inches Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Not established
Body Diameter: 0.105 inches Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Length:
D.105 inches Body Length: D.281 inches Power Dissipation Rating In Watts: D.050 free air Cubic Measure (non-core): D.002 cubic inches Style Designator: Axial terminal each end Test Data Document: D6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	2.000 inches
Body Length: 0.281 inches Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Body Diameter:
Double National Power Dissipation Rating In Watts: Double Measure (non-core): Double	0.105 inches
Power Dissipation Rating In Watts: 0.050 free air Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Length:
Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.281 inches
Cubic Measure (non-core): 0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
0.002 cubic inches Style Designator: Axial terminal each end Test Data Document: 0.6481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.050 free air
Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Cubic Measure (non-core):
Axial terminal each end Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	0.002 cubic inches
Test Data Document: 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization:	06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
A001a0	A001a0