## NSN 5905-00-401-9308

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-401-9308

Electrical Resistance: 6.400 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Full Rated Power:  125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established
Terminal Type:  Wire lead  Reliability Indicator:  Not established
Wire lead  Reliability Indicator:  Not established
Reliability Indicator: Not established
Not established
Terminal Length:
2.000 inches
Body Diameter:
0.105 inches
Body Length:
0.281 inches
Power Dissipation Rating In Watts:
0.050 free air
Cubic Measure (non-core):
0.002 cubic inches
Style Designator:
Axial terminal each end
Test Data Document:
06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A001a0