NSN 5905-00-402-0990

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-402-0990

Tompurature Coefficient Of Resistance in Ppm Per Deg Celsius: -10.00/41.00 Electrical Resistance: -11.000 kilohms Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -145.0 Tompurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Intelosure Method: Encospulated Terminal Type:	
Electrical Resistance: 11.000 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.000 inches Body Diameter: -0.141 inches Body Length: -0.391 inches Power Dissipation Rating in Watts: -0.100 ree air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
11.000 kilohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.000 inches Body Diameter: -0.141 inches Body Length: -0.391 inches Power Dissipation Rating In Watts: -0.100 ree air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Nea Unit Of Measure:	-10.0/+10.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Diameter: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Avial terminal each end Test Data Document: 06481-980532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Electrical Resistance:
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 0.441 servin all each end Test Data Document: 0.4584 -900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	11.000 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 for eair Style Designator: Axial terminal each end Test Data Document: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Filg:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.1100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 fee air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	145.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating in Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
1.000 inches Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.000 inches
Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
O.391 inches Power Dissipation Rating In Watts: O.100 free air Style Designator: Axial terminal each end Test Data Document: O6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.141 inches
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.100 free air Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.391 inches
Style Designator: Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.100 free air
Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0