

View Online at <https://aerobasegroup.com/nsn/5905-00-402-1156>

Section Quantity:

1

Body Style:

Rectangular w/pointer adjustment

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Overall Height:

1.078 inches

Body Length:

0.328 inches

Body Width:

0.516 inches

Body Height:

0.578 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Center To Center Distance Between Terminals:

0.200 inches

End Application:

Ticonderoga class cg (47); nimitz class cvn; los angeles class ssn (688); sturgeon class ssn (637); austin ship class lpd-4 amphibious transport docks; missile, air-to-air, phoenix (aim-54); virginia class cgn (41); sirius class t-afs 8; Forrestal class cv; Spruance class dd (963)

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Electrical Resistance Per Section:

200.0 ohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-70.0 to 70.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Actuator Travel Control Feature:

Continuous motion

Criticality Code Justification:

Feat

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0