

View Online at <https://aerobasegroup.com/nsn/5905-00-402-7358>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.516 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

Between 0.1245 inches and 0.1250 inches

**Shaft Length:**

0.500 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.016 inches

**Overall Diameter:**

0.750 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

2.50 inch-ounces

**Maximum Stop Torque:**

32.00 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.188 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

5.5 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

320.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0 to 30.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Precious Material And Location:**

Terminal surfaces gold and terminal surfaces silver

**Precious Material:**

Gold and silver

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0