NSN 5905-00-403-2250

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-403-2250

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|
| -15.0/+15.0 |
| Electrical Resistance: |
| 16.500 kilohms |
| Resistance Tolerance In Percent: |
| -0.100/+0.100 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 145.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 2.000 inches |
| Body Diameter: |
| 0.150 inches |
| Body Length: |
| 0.281 inches |
| Power Dissipation Rating In Watts: |
| 0.050 free air |
| Cubic Measure (non-core): |
| 0.002 cubic inches |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |
| |