## NSN 5905-00-403-2574

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-403-2574

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -15.0/+15.0   |
| Electrical Resistance:  |
| 10.100 kilohms  |
| Resistance Tolerance In Percent:  |
| -0.100/+0.100   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 125.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 145.0   |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 2.000 inches  |
| Body Diameter:  |
| 0.105 inches  |
| Body Length:  |
| 0.281 inches  |
| Power Dissipation Rating In Watts:  |
| 0.050 free air  |
| Cubic Measure (non-core):   |
| 0.002 cubic inches  |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 06481-912115 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |
|   |