NSN 5905-00-403-2885

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-2885 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.360 inches **Terminal Length:** 0.593 inches **Overall Height:** 0.952 inches **Overall Width:** 0.250 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.060 inches **Shaft Length:** 0.125 inches **Body Length:** 1.300 inches **Body Width:** 0.250 inches **Body Height:** 0.359 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Maximum Running Torque:** 8.00 inch-ounces **Center To Center Distance Between Terminals:** 0.700 inches **Lateral Distance Between Mounting Hole Centers:** 1.000 inches

Mounting Facility Quantity:

Terminal Location:

Lower adjacent side two rows

NSN 5905-00-403-2885

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.105 inches
Electrical Resistance Per Section:
1.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No