## NSN 5905-00-403-2887

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-2887

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.360 inches
Terminal Length:
0.593 inches
Overall Height:
0.952 inches
Overall Width:
0.250 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.060 inches
Shaft Length:
0.125 inches
Body Length:
1.300 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Running Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
0.700 inches
<b>Lateral Distance Between Mounting Hole Centers:</b>
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows

Lower adjacent side two rows

## NSN 5905-00-403-2887

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.105 inches
Electrical Resistance Per Section:
250.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No