NSN 5905-00-403-3032

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-3032 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.562 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1080.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.80 inch-ounces **Maximum Stop Torque:** 60.00 inch-ounces

Shaft End Play: 0.010 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.004 inches **Pilot Diameter Runout:** 0.004 inches

NSN 5905-00-403-3032

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
1080.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
00/00: 1
-3.0/+3.0 single section
-3.0/+3.0 single section Actuator Travel Control Feature:
•
Actuator Travel Control Feature:
Actuator Travel Control Feature: Stops
Actuator Travel Control Feature: Stops Function Characteristic Per Section:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure:
Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: