NSN 5905-00-403-3617

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-403-3617

Electrical Resistance: 2.150 kilohms Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
2.150 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -1.25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -1.75.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: -Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -155.0/+175.0 Inclosure Method:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator:
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Terminal Type: Wire lead Reliability Indicator:
Wire lead Reliability Indicator:
Reliability Indicator:
·
Established
Reliability Failure Rate Level In Percent:
0.001
Body Diameter:
0.109 inches
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0