Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-3633

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### Body Length:

0.593 inches

#### **Body Width:**

0.156 inches

**Body Height:** 

0.733 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

260.0

#### **Terminal Location:**

Lower adjacent side single row

## Mounting Method:

Tab

### **Electrical Resistance Per Section:**

1.0 kilohms single section

### Rotary Actuator Travel In Angular Deg:

260.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

### Power Dissipation Rating Per Section In Watts:

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 single section

### Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

## Shelf Life:

N/a

## Unit Of Measure:

---



Demilitarization:

No

Fiig:

A002a0