NSN 5905-00-403-4472

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-403-4472

Electrical Resistance: 287.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: -6.000 -6.	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.0004-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/-175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Akial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-50.0/+50.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: -0.001 Body Diameter: -0.125 inches Body Length: -0.375 inches Power Dissipation Rating in Watts: -0.125 free air Style Designator:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0/175.0 Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	287.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 inches Style Designator: Axial terminal each end Test Data Document: 81349-milit55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milf55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.126 free air Style Designator: Axial terminal each end Test Data Document: Bal349-milir55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milir55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	175.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-55.0/+175.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Wire lead
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Established
Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Reliability Failure Rate Level In Percent:
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.001
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Body Diameter:
O.375 inches Power Dissipation Rating In Watts: O.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.125 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.375 inches
Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.125 free air
Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Style Designator:
81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: 	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization	Unit Of Measure:
Demilitarization:	
Dennikanzanon.	Demilitarization:
No	No
Fiig:	Fiig:
A001a0	A001a0