## NSN 5905-00-403-7403

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-7403 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.500 inches **Body Diameter:** 1.391 inches **Shaft Diameter:** 0.248 inches Shaft Length: 0.750 inches **Body Length:** 0.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.375 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** 

Standard bushing

Electrical Resistance Per Section:
4.0 kilohms single section

## NSN 5905-00-403-7403

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
285.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0