NSN 5905-00-403-7405

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-403-7405

Section Quantity:
1
Shaft Diameter:
0.250 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.348 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Nonmetallic shaft and humidity proof
Electrical Resistance Per Section:
500.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
283.0
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-403-7405

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0