NSN 5905-00-404-0912

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-404-0912

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.500 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.141 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
10800.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Tab
Electrical Resistance Per Section:
250.0 ohms single section
Rotary Actuator Travel In Angular Deg:
10800.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-25.0 to 25.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
EE O significant and the second and

55.0 single section

NSN 5905-00-404-0912

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0