## NSN 5905-00-405-0569

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-0569

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.578 inches and 1.610 inches
Overall Height:
0.407 inches
Overall Width:
0.375 inches
Shaft Diameter:
0.115 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.344 inches
Body Width:
0.375 inches
Body Height:
0.407 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6120.0 and 9720.0
Maximum Starting Torque:
8.00 inch-ounces
Screw Thread Diameter:
0.216 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
28.0
Terminal Location:
Lower adjacent side single row

**Mounting Method:** Standard bushing

## NSN 5905-00-405-0569

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.0 ohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
0.7 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0