Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-0736

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Body Length:

0.179 inches

Body Width:

0.532 inches

Body Height:

0.699 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Tab

Features Provided:

Grounded contact arm

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

270.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0