Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-0761

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
1.125 inches
Shaft Style:
Round
Contact Arm Electrical Off Position:
Fully extended
Actuator Type:
Single shaft
Nonturn Device Location:
At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
160.000 ohms single section
Power Dissipation Rating Per Section In Watts:
25.6 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 20.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5905-00-405-0761

Nonprecision Wire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

