## NSN 5905-00-405-0761

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-0761 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.125 inches **Shaft Style:** Round **Contact Arm Electrical Off Position:** Fully extended **Actuator Type:** Single shaft **Nonturn Device Location:** At 3 oclock or at 6 oclock or at 9 oclock or at 12 oclock **Nonturn Device Radius:** 0.500 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 160.000 ohms single section **Power Dissipation Rating Per Section In Watts:** 25.6 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 20.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5905-00-405-0761

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0