## NSN 5905-00-405-2485

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-2485 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.357 inches **Terminal Length:** 0.187 inches **Body Diameter:** 0.250 inches **Body Length:** 0.180 inches **Overall Diameter:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 20.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section

Resistance Tolerance Per Section In Percent: -20.0 to 20.0 single section

## NSN 5905-00-405-2485

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0