Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-2784

Section Quantity:

1

Body Style:

Rectangular w/mounting holes

Mounting Hole Diameter:

0.093 inches

Body Length:

0.500 inches

Body Width:

0.187 inches

Body Height:

0.500 inches

Actuator Type:

Flush drive with slot-hole

Lateral Distance Between Mounting Hole Centers:

0.520 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Slot

Electrical Resistance Per Section:

5.000 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

160.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0 to 25.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-00-405-2784

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0