NSN 5905-00-405-3664

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-3664 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.812 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 2.000 inches **Overall Diameter:** 2.500 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Shaft End Play:** 0.003 inches **Shaft Runout:** 0.0005 inches **Lateral Runout:**

Pilot Diameter Runout:

0.062 inches

0.003 inches

NSN 5905-00-405-3664

Precision Wire Wound Variable Resistor - Page 2 of 2



| Shaft Radial Play: |
|---|
| 0.003 inches |
| Mechanical Backlash In Deg Angular Rotation: |
| 1.5 |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Locking bushing |
| Electrical Resistance Per Section: |
| 10.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 3600.0 |
| Function Conformity Tolerance Per Section: |
| -0.50/+0.50 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 5.0 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Continuous motion |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0