Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-3714

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Overall Length:

0.870 inches

Terminal Length:

0.130 inches

Overall Height:

0.440 inches

Overall Width:

0.160 inches

Shaft Diameter:

0.110 inches

Shaft Length:

0.120 inches

Body Length:

0.750 inches

Body Width:

0.160 inches

Body Height:

0.310 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

5400.0

Center To Center Distance Between Terminals:

0.500 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

NSN 5905-00-405-3714

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 5400.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.300 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0 to 50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Precious Material And Location:** Terminals gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A002a0