## NSN 5905-00-405-3768

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-405-3768

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9750 inches
Pilot Length:
0.0620 inches
Overall Length:
2.548 inches
Undercut Diameter:
1.062 inches
Undercut Width:
0.0500 inches
Body Diameter:
1.06200 inches
Shaft Diameter:
0.12480 inches
Shaft Length:
0.720 inches
Body Length:
0.500 inches
Overall Diameter:
1.062 inches
Mounting Lip Diameter:
1.0000 inches
Mounting Lip Depth:
0.0900 inches
Shaft Style:
Round, slotted
Actuator Type:
Double ended shaft
Shaft End Play:
0.00400 inches
Shaft Runout:
0.010 inches
Lateral Runout:
0.010 inches
Shaft Radial Play:
0.001 inches

## NSN 5905-00-405-3768

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Nonmetallic shaft and humidity proof
Electrical Resistance Per Section:
2.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0