NSN 5905-00-406-0503

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-406-0503

Section Quantity:
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.375 inches
Body Diameter:
0.937 inches
Shaft Diameter:
Between 0.2475 inches and 0.2495 inches
Shaft Length:
0.688 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.687 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
265.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
285.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Pom Per Deg Celsius:

-250.0 to 250.0 single section

NSN 5905-00-406-0503

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating	Per	Section	ln '	Watts:
-------------------	--------	-----	---------	------	--------

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0