NSN 5905-00-406-9169

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-406-9169 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.500 inches **Undercut Width:** 0.0930 inches **Body Diameter:** 1.656 inches **Shaft Diameter:** 0.124 inches **Shaft Length:** 0.750 inches **Body Length:** 1.742 inches **Mounting Lip Diameter:** 1.8120 inches **Mounting Lip Depth:** 0.0730 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 1.80 inch-ounces **Maximum Running Torque:** 1.35 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:**

0.002 inches **Lateral Runout:** 0.0015 inches

NSN 5905-00-406-9169

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Flange
Electrical Resistance Per Section:
10.0 kilohms all sections
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
113.7 all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary finish
Function Conformity Per Section:
All sections absolute linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-0.5/+0.5 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-00-406-9169

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0