## NSN 5905-00-407-0067

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-407-0067 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Diameter:** 0.495 inches **Body Length:** 0.345 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Actuator Travel Control Feature:** 

Stops

## NSN 5905-00-407-0067

**Fiig:** A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No