

View Online at https://aerobasegroup.com/nsn/5905-00-407-0331

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.125 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.922 inches

#### Mounting Bushing Length:

0.422 inches

#### Body Length:

0.531 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

340.0

#### Nonturn Device Location:

At 12 oclock

#### Nonturn Device Radius:

0.250 inches

#### Screw Thread Diameter:

0.375 inches

#### **Screw Thread Series Designator:**

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

## **Electrical Resistance Per Section:**

10.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

340.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

# NSN 5905-00-407-0331 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.5 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

#### Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0